


ARMY RESEARCH LABORATORY



An Initial Assessment of the Fit,
Retention, and Visual Display
Characteristics of the Kaiser Proview™
Head-Mounted Display System

David B. Durbin

ARL-TN-135

MARCH 1999

19990526 085

DTIC QUALITY INSPECTED 1

Approved for public release; distribution is unlimited.

MetaVR™ is a trademark of MetaVR.

ProView™ is a trademark of Kaiser Electro-Optics, Inc.

SPSS® is a registered trademark of Statistical Program for the Social Sciences, Inc.

The findings in this report are the official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Abstract

Head-mounted displays (HMDs) are a potentially viable technology for presentation of the “out-the-window” (OTW) scene for Army aviation simulators. As part of an effort to evaluate their suitability for Army aviation, a preliminary assessment of three Kaiser ProView™ HMDs was conducted during a simulation exercise at the U.S. Army Aviation Test Bed, Fort Rucker, Alabama. The assessment evaluated the fit, retention, and visual display characteristics of the HMDs. The method used to assess the HMDs included aviator responses to a usability survey, statistical correlation of survey responses with head measurements obtained from each aviator, observation of aviator performance during their missions, and post-mission interviews. Most of the fit, retention, and visual display characteristics of the HMDs were judged to be acceptable by the Army aviators. Suitability of the HMDs would be improved by an increase in field of view and the use of lightweight electrical cables to minimize restriction of head movement and potential for pressure-induced hot spots.

CONTENTS

EXECUTIVE SUMMARY	3
INTRODUCTION	5
Purpose	5
System Description	5
METHOD	6
Subjects	6
Procedure	7
Data Collection	8
Anthropometry	9
Data Analysis	10
Limitations of Assessment	10
RESULTS	10
Fit and Retention	10
Visual Display Characteristics	11
CONCLUSIONS	12
RECOMMENDATIONS	12
REFERENCES	13
APPENDICES	
A. Correlation of Head Measurements With Aviator Survey Responses Regarding Fit and Retention of HMDs	15
B. Aviator Survey Responses Regarding Fit and Retention of HMDs	19
C. Aviator Survey Responses Regarding Visual Characteristics of HMDs	23
D. Summary of Aviator Responses Regarding Fit, Retention, and Visual Display Characteristics of HMDs	27
E. Aviator Survey Responses Regarding Motion Sickness Symptoms Experienced During Mission	31
F. Total Hours Each Aviator Had Used an HMD Before Assessment	35
DISTRIBUTION LIST	39
REPORT DOCUMENTATION PAGE	45

FIGURES

1. Kaiser ProView™ 40 HMD	2
2. Mission Route for HMD Simulation Exercise	8

TABLES

1. Demographic Characteristics of Aviators	6
2. Head Measurements of Aviators	9

EXECUTIVE SUMMARY

Head-mounted displays (HMDs) have potential benefits for use as the “out-the-window” (OTW) display for Army aviation flight simulators because of their small size and weight, transportability, and comparatively low costs. However, the human factors characteristics associated with the usability of HMDs as OTW displays have yet to be fully identified and evaluated. A preliminary assessment of three Kaiser ProView™ HMDs was conducted on 8 and 9 October 1998, at the U.S. Army Aviation Test Bed, Fort Rucker, Alabama. The assessment was requested by the Directorate of Training, Doctrine, and Simulation, U.S. Army Aviation Center, Fort Rucker, Alabama, and evaluated the fit, retention, and visual display characteristics of the HMDs during a mission simulation exercise. The assessment was based on aviator responses to a usability survey, statistical correlation of survey responses with head measurements obtained from each aviator, observation of aviator performance during their missions, and post-mission interviews. This report contains a description of the assessment and its findings. Most of the fit, retention, and visual display characteristics of the HMDs were rated as positive by the aviators. The usability of the HMDs would be enhanced by an increased field of view and the use of lightweight electrical cables to minimize restriction of head movement and potential for hot spots.

AN INITIAL ASSESSMENT OF THE FIT, RETENTION, AND VISUAL DISPLAY CHARACTERISTICS OF THE KAISER PROVIEW™ HEAD-MOUNTED DISPLAY SYSTEM

INTRODUCTION

Purpose

Army aviation is becoming increasingly reliant on simulation to maintain training proficiency for aircrews. Several research efforts are evaluating the training effectiveness of various simulation display technologies, including head-mounted displays (HMDs). HMDs have potential benefits for use as the “out-the-window” (OTW) display for flight simulators because of their small size and weight, transportability, and comparatively low costs. However, the human factors characteristics associated with the usability of HMDs as OTW displays have yet to be fully identified and evaluated. The purpose of this assessment was to conduct an initial evaluation of the fit, retention, and visual characteristics of three Kaiser ProView™ HMDs during a simulation exercise in the Aviation Test Bed, Fort Rucker, Alabama. This assessment was requested by the Directorate of Training, Doctrine, and Simulation and provides useful insights about the usability of HMDs as the OTW display for Army aviation flight simulators.

System Description

The three HMDs were models with 40°, 50°, or 60° fields of view (FOVs) (diagonal), dual liquid crystal displays on which the OTW scene was projected, an adjustable headband made of semi-rigid plastic, and a lightweight, inertial head tracker mounted on top of the headband (see Figure 1). The resolution of the liquid crystal displays was 640 by 480 pixels. Electrical connections were bundled into a single cable that attached to the lower back of the headband. The HMDs provided user adjustments for display brightness, interpupillary distance, eye relief, and vertical display alignment. The approximate weight of the HMDs was 1.3 pounds for the ProView™ 40 and 50 and 1.7 pounds for the ProView™ 60. During the simulation exercise, the HMDs were interfaced with a MetaVR™ image generator that provided an OTW visual scene (terrain and man-made objects) portrayed to the aviators on the liquid crystal displays.




Figure 1. Kaiser ProView™ 40 HMD.

METHOD

Subjects

Subjects were eight males who were current or former Army aviators. They represented a group of highly experienced aviators with an average of 4,300 hours of flight time in Army aircraft. Five of the aviators also had significant experience using HMDs in a simulation environment. Their relevant demographic characteristics are listed in Table 1.

Table 1
Demographic Characteristics of Aviators
(N = 8 males)

Summary of demographic characteristics	Age (years)	Total flight hours	Total hours aviators have used an HMD to date ^a	Corrective lens worn during assessment
Mean	44.3	4300	203.9 ^b	Yes—37% ^c
Range	37 to 52	1800 to 6000	1.2 to 1200	No—63%

^aSee Appendix F for total HMD hours for each aviator

^bMedian total hours = 26.0

^cThree aviators wore eyeglasses


Procedure

The assessment was conducted using the HMDs in a fully reconfigurable experimental device (FRED) simulator located in the Aviation Test Bed, Fort Rucker, Alabama. The FRED simulators are used primarily for collective task training by the U.S. Army Aviation Center. They contain generic helicopter flight controls, provide the OTW scene on five 60-inch monitors, and can be configured to functionally represent the AH-64, OH-58C or D, and UH-60 helicopters. The FRED simulator used for the HMD simulation exercise was configured to represent an AH-64. The 60-inch monitors were turned off for the exercise because the HMD provided the OTW scene.

Before entering the simulators to begin their mission, the aviators were briefed about the purpose of the assessment, and their heads were measured (see Table 2) by personnel from the Human Research and Engineering Directorate (HRED) of the U.S. Army Research Laboratory (ARL). In addition, Kaiser personnel provided each aviator with a "hands-on" demonstration of the method for adjusting the HMD to fit his head and the method for adjusting the position of the displays. The aviators then entered the simulator, were asked to don the HMDs, perform necessary adjustments to accommodate their head sizes, and begin their mission.

During the assessment, one aviator flew the simulator in the pilot's seat while the other aviator sat in the copilot-gunner's (CP/G) seat and attempted to acquire and engage targets. A contractor sat in a third seat close to the pilot's seat to help with HMD adjustments and to troubleshoot technical problems that arose during the simulation. The aviator sitting in the CP/G seat wore the ProView™ 60, while the aviator sitting in the pilot seat wore the ProView™ 40 or 50. At the mid-point of the mission, the aviators switched seats in order to wear the other HMD models during the mission.

The aviators flew a mission route (see Figure 2) from a forward assembly area (FAA) to a battle position (BP), attempted to acquire and engage targets in the engagement area (EA), and then returned to the FAA. In order to maximize the aviators' exposure to different visual scenes, while they wore the HMDs, two different terrain databases were used during the mission. On the outbound leg of the mission, a hilly terrain database with moderate vegetation was used. On the inbound leg of the mission (after departure from the EA), a desert terrain database modeled after the National Training Center, Fort Irwin, California, was used. Upon completion of their mission, the aviators exited the simulator, were interviewed by ARL personnel, and completed an 11-page survey regarding their assessment of the fit, retention, and visual characteristics of the HMDs.



The aviators spent an average of 74 minutes in the simulator performing their mission while wearing the HMDs. Seven aviators wore their flight suits during the assessment, while the eighth wore civilian clothes. The ambient temperature in the simulator during the assessment varied between 66° and 69° F. Incident light levels in the simulator were measured at less than 10.0 lux (< 1.0 footcandle).

The methodology used by ARL (HRED) personnel to collect human factors data included obtaining head measurements from each aviator, administering a usability survey, observing aviator performance during their missions, and interviewing the aviators after they completed their flight. The survey was developed in accordance with published guidelines for proper format and content (Babbitt & Nystrom, 1989; Georgia Institute of Technology, 1994). A brief pre-test was conducted to refine the survey and to establish its content and face validity. Survey results were augmented and clarified with observations recorded during missions and with information obtained during aviator interviews. Because the fit, retention, and visual display

characteristics were essentially identical (except for FOV) for the ProView™ 40, 50, and 60 HMDs, the aviators completed one survey that addressed all three HMDs. The aviators reported that differences in the FOV between the HMDs were not noticeable and did not affect the HMDs' performance. Observations of aviator performance during their missions and a hands-on evaluation of the HMDs by ARL personnel supported the aviators' judgments that the differences in FOV were not noticeable. In the few instances when aviators noted minor differences among the three HMDs, they reported the differences on the survey.

Anthropometry

Head measurements (see Table 2) were obtained from each aviator for four anthropometric dimensions including head length, breadth, and circumference, and interpupillary breadth. The measurements were obtained in accordance with published procedures (Gordon et al., 1989) and were used to determine how well the HMDs accommodated the range of the aviators' head sizes. This was accomplished by constructing a correlation matrix (see Appendix A) matching the aviators' head measurements with their survey responses in order to determine any statistically significant relationships. For example, correlation coefficients were computed to determine whether aviators with larger head sizes reported significantly more (or fewer) problems with HMD stability than did aviators with smaller head sizes. The upper percentile ranks for male soldiers were well represented for head breadth, length, and circumference. The lower percentile rank for female and male soldiers was represented for interpupillary breadth. Three aviators wore eyeglasses. This allowed an assessment of how well the eye relief adjustment on the HMDs accommodated eyeglasses and whether there were any optical distortions because eyeglasses were worn.

Table 2
Head Measurements of Aviators

Summary of aviator head measurement data	Head breadth (cm)	Head length (cm)	Head circumference (in.)	Interpupillary breadth (cm)
Mean	15.6	20.0	22.9	6.2
SD ^a	0.5	0.6	0.5	0.3
Range ψ (percentile)	14th to 97th	15th to 92nd	30th to 98th	1st to 65th ^b

^aSD = standard deviation

^b1st percentile male is equivalent to 3rd percentile female

ψ Range for Army male soldiers

Data Analysis

Survey data were entered into the Statistical Program for the Social Sciences (SPSS®) for reduction and analysis. Descriptive statistical data including percentages, averages (means), standard deviations, and medians were generated. The data were further analyzed using a chi-square goodness-of-fit test to determine any statistically significant response trends to survey items. These trends indicate that the responses provided by the aviators to a particular survey item were not random but were attributable to a systematic factor such as a strong like or dislike for a particular characteristic of the HMDs (e.g., display resolution). These trends increase the level of confidence that the aviators' responses are accurately measuring a usability characteristic of the HMDs. Because of the small number of aviators who were surveyed, an exact chi-square probability value was computed for each survey item. Additionally, a correlation matrix that matched aviator head measurement data with their survey responses was developed. This helped determine how well the fit and retention characteristics of the HMDs accommodated the aviators' range of head sizes.

Limitations of Assessment

Schedule and funding constraints precluded a comprehensive assessment of the Kaiser ProView™ HMDs. The entire simulation exercise lasted only 2 days. The amount of time available for aviator selection and training, flight time with the HMDs in the simulator, and data collection was very limited. Technical problems with the aviation test bed (AVTB) image generator resulted in noticeable image lag on the HMD visual scene and caused occasional system crashes. The aviators were annoyed by the technical problems, but they reported that it did not significantly alter their judgments about the fit, retention, and visual characteristics of the HMDs. They felt that the human factors characteristics pertaining to the fit, retention, and visual display were very apparent and were not obscured by image lag, occasional system crashes, or other technical problems.

RESULTS

Fit and Retention

Overall, the aviators reported that the fit and retention characteristics of the ProView™ 40, 50, and 60 HMDs were good (see Appendix B). In general, the HMDs

- were quick and easy to adjust,
- maintained adequate stability on the aviators' heads, even during quick head turns in the horizontal and vertical axes,

- did not cause uncomfortable head temperatures,
- had adequate eye relief adjustment to accommodate eyeglasses worn by aviators,
- seldom required adjustment of interpupillary distance during the mission for most of the aviators,
- had a comfortable center of gravity, and
- induced no upper body discomfort.

However, the aviators reported that the electrical cable that attached to the lower back of the HMDs partially restricted their head movement. Also, three aviators reported experiencing occasional hot spots on the back of their heads while wearing the ProView™ 60. These three aviators had larger head lengths and circumferences than the other aviators did. The correlation (see Appendix A) between their larger head lengths and circumferences and the reported frequency of hot spots was statistically significant [$p(r \geq .818) < .02$, head length], [$p(r \geq .799) < .02$, head circumference]. A likely explanation is that the weight of the electrical cable that attached to the lower back of the ProView™ 60 headband resulted in localized pressure on the back of the head of the aviators who had larger head lengths and circumferences.

Visual Display Characteristics

In general, the aviators reported that the resolution, brightness, and color of the images on the HMD liquid crystal displays were good (see Appendix C). Image flicker was infrequent and six of the eight aviators reported that the HMDs' visual scene provided good situational awareness of their immediate environment (e.g., terrain features). The three aviators who wore eyeglasses reported that they experienced no optical distortions when viewing the visual display. However, several aviators reported that the dynamic visual cues needed for flying the simulator at low altitude were less than adequate. These included depth of the visual field, rate of closure, altitude and attitude cues. The aviators reported that the limited FOV provided by the HMDs was a primary factor in contributing to their lack of adequate visual cues. The aviators also reported that the limited FOV was a significant factor in their rating the simulator as more difficult to fly than their actual aircraft. Most aviators did not experience motion sickness symptoms while wearing the HMDs. However, two aviators reported experiencing moderate symptoms of eye fatigue and nausea during their mission, and one aviator reported experiencing moderate symptoms of dizziness and nausea (see Appendix D). None of the aviators were forced to discontinue the mission because of their physiological discomfort. However, since the average mission duration

was only 74 minutes, further evaluation would be required to determine if wearing the HMDs for longer periods of time would induce more severe or disabling motion sickness symptoms.

CONCLUSIONS

The Kaiser ProView™ 40, 50, and 60 HMDs show promise for use as the OTW display for Army aviation flight simulators. The overall fit and retention characteristics of the HMDs were rated as positive by the aviators. Most of the visual display characteristics of the HMDs were also rated as positive. Additionally, ARL personnel observed that the aviators appeared to be visually “immersed” in the simulation environment throughout their mission. Note, however, that at low altitude, the visual scene displayed by the HMDs did not provide adequate visual cues for judging depth of field, rate of closure, and changes in altitude and attitude. The lack of adequate cueing appeared to be caused primarily by the limited FOV of the HMDs. Kaiser is currently developing an HMD with a 100° FOV (ProView™ 100) to help address this issue.

RECOMMENDATIONS

The limitations of the simulation exercise did not allow an in-depth evaluation of the human factors characteristics of the Kaiser ProView™ HMDs. However, the survey responses provided by the Army aviators serve as useful insights about the usability of HMDs as the OTW display for Army aviation flight simulators. The survey responses also identify potential design limitations that should be the focus of a comprehensive evaluation. It is recommended that additional evaluations be conducted to accomplish the following:

1. Quantify the impact that the human factors characteristics of HMDs have on training effectiveness;
2. Assess the use of HMDs in different operational environments (e.g., high ambient illumination); and
3. Assess the physiological and performance effects of wearing an HMD for extended periods of time (e.g., 2 to 4 hours).

To be effective, the evaluation must employ a large sample size of aviators with a wide range of experience and must assess representative 5th percentile female through 95th percentile male anthropometric dimensions. The evaluation also should investigate (a) different types of electrical cables and methods of routing the cables to minimize restriction of head movement and potential for induced hot spots, and (b) HMDs with larger FOVs (as they become commercially available).

REFERENCES

Babbitt, B., & Nystrom, C. (1989). Questionnaire construction manual. Fort Hood, TX: U.S. Army Research Institute.

Georgia Institute of Technology (1994). Method of test for characterization of helmet-mounted displays for the U.S. Army. Atlanta, GA: Author.

Gordon, C., Churchill, T., Clauser, C., Bradtmiller, B., McConville, J., Tebbetts, I., & Walker, R. (1989). 1988 anthropometric survey of U.S. Army personnel: Methods and summary statistics. Yellow Springs, OH: Anthropology Research Project.

APPENDIX A

CORRELATION OF HEAD MEASUREMENTS WITH AVIATOR SURVEY
RESPONSES REGARDING FIT AND RETENTION OF HMDS

**CORRELATION OF HEAD MEASUREMENTS WITH AVIATOR SURVEY
RESPONSES REGARDING FIT AND RETENTION OF HMDS**

	Head measurements			
Survey items regarding HMD fit and retention	Head breadth	Head length	Head circumference	Interpupillary distance
Ease of HMD adjustment before mission	.000	-.114	.114	.283
Time to adjust HMD	-.113	-.399	-.627	-.170
Center of gravity	.118	.438	.390	.387
Fore & aft stability of HMD	.311	.292	.536	.145
Side-to-side stability of HMD	.311	.292	.536	.145
Range of head movement	-.332	.417	.334	-.415
Hot spots	.243	.818*	.799*	-.007
Temperature	.567	.399	.456	.340
FOV adjustment	.113	.127	.317	.201
Neck comfort	.340	-.114	.171	.227
Shoulder comfort	.340	-.114	.171	.227
Upper back comfort	.340	-.114	.171	.227
Lower back comfort	.340	-.114	.171	.227
Arms comfort	.340	-.114	.171	.227

*Significant at $\alpha .05$

APPENDIX B

**AVIATOR SURVEY RESPONSES REGARDING FIT
AND RETENTION OF HMDS**

AVIATOR SURVEY RESPONSES REGARDING FIT AND RETENTION OF HMDS

Ease of HMD adjustment before mission*	Very difficult _____ 0%	Difficult _____ 0%	Borderline _____ 0%	Easy _____ 37%	Very easy _____ 63%
Time to adjust HMD*	< 2 min. _____ 63%	2 to 5 min. _____ 37%	6 to 9 min. _____ 0%	0 to 15 min. _____ 0%	> 15 min. _____ 0%
Center of gravity*	Very uncomfortable _____ 0%	Uncomfortable _____ 0%	Borderline _____ 12%	Comfortable _____ 63%	Very comfortable _____ 25%
Fore & aft stability*	Very unstable _____ 0%	Unstable _____ 0%	Borderline _____ 12%	Stable _____ 63%	Very stable _____ 25%
Side-to-side stability*	Very unstable _____ 0%	Unstable _____ 0%	Borderline _____ 12%	Stable _____ 63%	Very stable _____ 25%
Range of head movement*	Very restrictive _____ 0%	Somewhat restrictive _____ 88%	Not restrictive _____ 12%	_____ _____ 0%	_____ _____ 0%
Hot spots	Always _____ 0%	Most of time _____ 0%	Sometimes _____ 38%	Rarely _____ 12%	Very rarely _____ 50%
Temperature*	Very uncomfortable _____ 0%	Uncomfortable _____ 0%	Borderline _____ 0%	Comfortable _____ 37%	Very comfortable _____ 63%

*Significant at $\alpha .05$, indicating a non-random response trend

Interpupillary distance adjustment during mission	Frequently —— 12%	Sometimes —— 12%	Rarely —— 38%	Never —— 38%	——
<i>Upper body comfort</i>	Very uncomfortable	Uncomfortable	Borderline	Comfortable	Very comfortable
Neck comfort*	0%	0%	0%	63%	37%
Shoulders comfort*	0%	0%	0%	63%	37%
Upper back comfort*	0%	0%	0%	63%	37%
Lower back comfort*	0%	0%	0%	63%	37%
Arms comfort*	0%	0%	0%	63%	37%

*Significant at $\alpha .05$, indicating a non-random response trend

APPENDIX C

AVIATOR SURVEY RESPONSES REGARDING VISUAL
CHARACTERISTICS OF HMDS

AVIATOR SURVEY RESPONSES REGARDING VISUAL
CHARACTERISTICS OF HMDS

Sharpness of images displayed on HMD*	Very faded _____ 0%	Faded _____ 0%	Borderline _____ 25%	Sharp _____ 75%	Very sharp _____ 0%
Brightness of visual scene displayed on HMD*	Very inadequate _____ 0%	Inadequate _____ 0%	Borderline _____ 0%	Adequate _____ 88%	Very adequate _____ 12%
How often aviators experienced image lag on HMD	Always _____ 0%	Most of time _____ 25%	Sometimes _____ 25%	Rarely _____ 37%	Never _____ 12%
Color of displayed images on HMD*	Very inadequate _____ 0%	Inadequate _____ 0%	Borderline _____ 0%	Adequate _____ 88%	Very adequate _____ 12%
How often aviators noticed flickering of visual scene	Always _____ 0%	Most of time _____ 0%	Sometimes _____ 25%	Rarely _____ 50%	Never _____ 25%
Adequacy of visual scene on HMD for providing situational awareness*	Very inadequate _____ 0%	Inadequate _____ 25%	Borderline _____ 0%	Adequate _____ 75%	Very adequate _____ 0%
Ease of "flying" simulator using HMD visual scene versus flying actual aircraft	Much more difficult _____ 38%	More difficult _____ 50%	Same level of difficulty _____ 12%	Easier _____ 0%	Much Easier _____ 0%

*Significant at $\alpha .05$, indicating a non-random response trend

<i>Visual perception cues</i>	Very inadequate	Inadequate	Borderline	Adequate	Very adequate
Depth	0%	12%	50%	38%	0%
Range*	0%	12%	25%	63%	0%
Rate of closure*	0%	12%	76%	12%	0%
<i>Aircraft altitude and attitude cues (while flying at low altitude)</i>	Very inadequate	Inadequate	Borderline	Adequate	Very adequate
Altitude cues	0%	12%	38%	50%	0%
Attitude cues	0%	12%	38%	50%	0%

*Significant at $\alpha .05$, indicating a non-random response trend

APPENDIX D

SUMMARY OF AVIATOR RESPONSES REGARDING FIT, RETENTION, AND VISUAL DISPLAY CHARACTERISTICS OF HMDS


SUMMARY OF AVIATOR RESPONSES REGARDING FIT, RETENTION, AND VISUAL DISPLAY CHARACTERISTICS OF HMDS

<i>Fit and retention characteristics</i>	<i>Visual display characteristics</i>
<ul style="list-style-type: none"> • HMD was easy to adjust before mission. Adjustment took 62 seconds, on average. • Fore, aft, and side-to-side stability of HMD during mission was generally good. • HMD did not induce uncomfortable head temperature when worn. • Weight distribution (center of gravity) of the HMD on the aviator's head was reported as comfortable. • Most aviators seldom had to adjust the interpupillary distance of the displays during their mission. • Aviators who wore eyeglasses had adequate eye relief adjustment. • Wearing the HMD caused no upper body discomfort for neck, shoulders, back, or arms. • Three of eight aviators reported occasional problems with hot spots on the back of their head while wearing the ProView™ 60. • Range of head movement was somewhat restricted by cable on back of HMD. 	<ul style="list-style-type: none"> • Images displayed on the HMD had adequate resolution. • Brightness of the visual scene on the HMD was adequate. • Flickering of images on the HMD visual scene was minimal. • The color of the images displayed on the HMD was adequate. • The visual scene on the HMD provided most aviators with adequate situational awareness of their immediate environment. • Aviators who wore eyeglasses did not experience optical distortions of images on the display. • Most aviators did not experience motion sickness symptoms while wearing the HMDs. • Visual perception cues provided by the HMD for rate of closure and depth of visual field at low altitude were less than adequate for most aviators. • Aircraft altitude and attitude visual cues (at low altitude) were less than adequate for half of the aviators. • Image lag was often noticeable on the HMD visual scene because of problems with the AVTB image generator. • Most aviators reported that flying the simulator using the HMD was more difficult than flying an actual aircraft primarily because of limited FOV.

APPENDIX E

AVIATOR SURVEY RESPONSES REGARDING MOTION SICKNESS SYMPTOMS EXPERIENCED DURING MISSION

AVIATOR SURVEY RESPONSES REGARDING MOTION SICKNESS
SYMPTOMS EXPERIENCED DURING MISSION



APPENDIX F

TOTAL HOURS EACH AVIATOR HAD USED AN
HMD BEFORE ASSESSMENT

TOTAL HOURS EACH AVIATOR HAD USED AN
HMD BEFORE ASSESSMENT

Aviator No. 1	1200 hours*
Aviator No. 2	1.2 hours
Aviator No. 3	1.2 hours
Aviator No. 4	22 hours
Aviator No. 5	75 hours
Aviator No. 6	300 hours
Aviator No. 7	30 hours
Aviator No. 8	1.5 hours

*Aviator accrued hours as simulation pilot for the Army Research Institute

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	ADMINISTRATOR DEFENSE TECHNICAL INFO CENTER ATTN DTIC OCP 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	1	DEPUTY COMMANDING GENERAL ATTN EXS (Q) MARINE CORPS RD&A COMMAND QUANTICO VA 22134
1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL CS AL TA REC MGMT 2800 POWDER MILL RD ADELPHI MD 20783-1197	1	HEADQUARTERS USATRADO ATTN ATCD SP FORT MONROE VA 23651
1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL CI LL TECH LIB 2800 POWDER MILL RD ADELPHI MD 207830-1197	1	COMMANDER USATRADO COMMAND SAFETY OFFICE ATTN ATOS (MR PESSAGNO/MR LYNE) FORT MONROE VA 23651-5000
1	DIR FOR PERSONNEL TECHNOLOGIES DEPUTY CHIEF OF STAFF PERSONNEL 300 ARMY PENTAGON 2C733 WASHINGTON DC 20310-0300	1	DIRECTOR TDAD DCST ATTN ATTG C BLDG 161 FORT MONROE VA 23651-5000
1	OUSD(A)/DDDR&E(R&A)/E&LS PENTAGON ROOM 3D129 WASHINGTON DC 20301-3080	1	COMMANDER USA OPERATIONAL TEST & EVAL AGENCY ATTN CSTE TSM 4501 FORD AVE ALEXANDRIA VA 22302-1458
1	CODE 1142PS OFFICE OF NAVAL RESEARCH 800 N QUINCY STREET ARLINGTON VA 22217-5000	1	USA BIOMEDICAL R&D LABORATORY ATTN LIBRARY FORT DETRICK BUILDING 568 FREDERICK MD 21702-5010
1	WALTER REED ARMY INST OF RSCH ATTN SGRD UWI C (COL REDMOND) WASHINGTON DC 20307-5100	1	HQ USAMRDC ATTN SGRD PLC FORT DETRICK MD 21701
1	DR ARTHUR RUBIN NATL INST OF STANDARDS & TECH BUILDING 226 ROOM A313 GAITHERSBURG MD 20899	1	COMMANDER USA AEROMEDICAL RESEARCH LAB ATTN LIBRARY FORT RUCKER AL 36362-5292
1	COMMANDER US ARMY RESEARCH INSTITUTE ATTN PERI ZT (DR E M JOHNSON) 5001 EISENHOWER AVENUE ALEXANDRIA VA 22333-5600	1	US ARMY SAFETY CENTER ATTN CSSC SE FORT RUCKER AL 36362
1	DEFENSE LOGISTICS STUDIES INFORMATION EXCHANGE ATTN DIRECTOR DLSIE ATSZ DL BLDG 12500 2401 QUARTERS ROAD FORT LEE VA 23801-1705	1	CHIEF ARMY RESEARCH INSTITUTE AVIATION R&D ACTIVITY ATTN PERI IR FORT RUCKER AL 36362-5354
		1	AIR FORCE FLIGHT DYNAMICS LAB ATTN AFWAL/FIES/SURVIAC WRIGHT PATTERSON AFB OH 45433

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	US ARMY NATICK RD&E CENTER ATTN STRNC YBA NATICK MA 01760-5020	1	USA TRADOC ANALYSIS COMMAND ATTN ATRC WSR (D ANGUIANO) WHITE SANDS MISSILE RANGE NM 88002-5502
1	US ARMY TROOP SUPPORT CMD NATICK RD&E CENTER ATTN BEHAVIORAL SCI DIV SSD NATICK MA 01760-5020	1	STRICOM 12350 RESEARCH PARKWAY ORLANDO FL 32826-3276
1	US ARMY TROOP SUPPORT CMD NATICK RD&E CENTER ATTN TECH LIBRARY (STRNC MIL) NATICK MA 01760-5040	1	COMMANDER USA TANK-AUTOMOTIVE R&D CENTER ATTN AMSTA RS/D REES WARREN MI 48090
1	DR RICHARD JOHNSON HEALTH & PERFORMANCE DIVISION US ARIEM NATICK MA 01760-5007	1	COMMANDER USA COLD REGIONS TEST CENTER ATTN STECR TS A APO AP 96508-7850
1	LOCKHEED SANDERS INC BOX MER 24 1583 NASHUA NH 03061-0868	1	PURDUE UNIVERSITY SERIALS UNIT CDM KARDEX 1535 STEWART CENTER WEST LAFAYETTE IN 47907-1535
1	MEDICAL LIBRARY BLDG 148 NAVAL SUBMARINE MEDICAL RSCH LAB BOX 900 SUBMARINE BASE NEW LONDON GROTON CT 06340	1	GOVT PUBLICATIONS LIBRARY 409 WILSON M UNIVERSITY OF MINNESOTA MINNEAPOLIS MN 55455
1	USAF ARMSTRONG LAB/CFTO ATTN DR F WESLEY BAUMGARDNER SUSTAINED OPERATIONS BRANCH BROOKS AFB TX 78235-5000	1	DR RICHARD PEW BBN SYSTEMS AND TECH CORP 10 MOULTON STREET CAMBRIDGE MA 02138
1	ARI FIELD UNIT FORT KNOX BUILDING 2423 PERI IK FORT KNOX KY 40121-5620	1	DR HARVEY A TAUB RSCH SECTION PSYCH SECTION VETERANS ADMIN HOSPITAL IRVING AVENUE & UNIVERSITY PLACE SYRACUSE NY 13210
1	COMMANDANT USA ARTILLERY & MISSILE SCHOOL ATTN USAAMS TECH LIBRARY FORT SILL OK 73503	1	DR ROBERT C SUGARMAN 132 SEABROOK DRIVE BUFFALO NY 14221
1	COMMANDER WHITE SANDS MISSILE RANGE ATTN STEWS TE RE WHITE SANDS MISSILE RANGE NM 88002	1	DR ANTHONY DEBONS IDIS UNIVERSITY OF PITTSBURGH PITTSBURGH PA 15260
1	COMMANDER WHITE SANDS MISSILE RANGE ATTN TECHNICAL LIBRARY WHITE SANDS MISSILE RANGE NM 88002	1	MR R BEGGS BOEING-HELICOPTER CO P30-18 PO BOX 16858 PHILADELPHIA PA 19142

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DR ROBERT KENNEDY ESSEX CORPORATION SUITE 227 1040 WOODCOCK ROAD ORLANDO FL 32803	1	MR KENNETH C CROMBIE TECHNICAL LIBRARIAN E104 DELCO SYSTEMS OPERATIONS 6767 HOLLISTER AVENUE GOLETA CA 93117
1	DR NANCY ANDERSON DEPARTMENT OF PSYCHOLOGY UNIVERSITY OF MARYLAND COLLEGE PARK MD 20742	1	MR WALT TRUSZKOWSKI NASA/GODDARD SPACE FLIGHT CENTER CODE 588.0 GREENBELT MD 20771
1	DR BEN B MORGAN DEPARTMENT OF PSYCHOLOGY UNIVERSITY OF CENTRAL FLORIDA PO BOX 25000 ORLANDO FL 32816	1	DIRECTOR US ARMY AEROFIGHT DYNAMICS DIR ATTN SAVRT AF D (A W KERR) AMES RESEARCH CENTER (MS 215-1) MOFFETT FIELD CA 94035-1099
1	LAWRENCE C PERLMUTER PHD UNIV OF HEALTH SCIENCES THE CHICAGO MEDICAL SCHOOL DEPT OF PSYCHOLOGY 3333 GREEN BAY ROAD NORTH CHICAGO IL 60064	1	DR NORMAN BADLER DEPT OF COMPUTER & INFORMATION SCIENCE UNIVERSITY OF PENNSYLVANIA PHILADELPHIA PA 19104-6389
1	DR ARTHUR S KAMLET BELL LABORATORIES 6200 EAST BROAD STREET COLUMBUS OH 43213	1	COMMANDER US ARMY RESEARCH INSTITUTE OF ENVIRONMENTAL MEDICINE NATICK MA 01760-5007
1	GENERAL MOTORS CORPORATION NORTH AMERICAN OPERATIONS PORTFOLIO ENGINEERING CENTER HUMAN FACTORS ENGINEERING ATTN MR A J ARNOLD STAFF PROJ ENG ENGINEERING BLDG 30200 MOUND RD BOX 9010 WARREN MI 48090-9010	1	HQDA (DAPE ZXO) ATTN DR FISCHL WASHINGTON DC 20310-0300
1	GENERAL DYNAMICS LAND SYSTEMS DIV LIBRARY PO BOX 1901 WARREN MI 48090	1	HUMAN FACTORS ENG PROGRAM DEPT OF BIOMEDICAL ENGINEERING COLLEGE OF ENGINEERING & COMPUTER SCIENCE WRIGHT STATE UNIVERSITY DAYTON OH 45435
1	DR LLOYD A AVANT DEPARTMENT OF PSYCHOLOGY IOWA STATE UNIVERSITY AMES IA 50010	1	COMMANDER USA MEDICAL R&D COMMAND ATTN SGRD PLC (LTC K FRIEDL) FORT DETRICK MD 21701-5012
1	DR MM AYOUB DIRECTOR INST FOR ERGONOMICS RESEARCH TEXAS TECH UNIVERSITY LUBBOCK TX 79409	1	PEO STANDARD ARMY MGMT INFORMATION SYSTEM ATTN AS PES STOP C-3 FT BELVOIR VA 22060-5456
		1	PEO ARMORED SYS MODERNIZATION US ARMY TANK-AUTOMOTIVE CMD ATTN SFAE ASM S WARREN MI 48397-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	PEO COMBAT SUPPORT ATTN AMCPEO CS US ARMY TANK AUTOMOTIVE CMD WARREN MI 48397-5000	1	COMMANDANT US ARMY ARMOR SCHOOL ATTN ATSB CDS (MR LIPSCOMB) FT KNOX KY 40121-5215
1	PEO INTELLIGENCE & ELECTRONIC WARFARE ATTN AMCPEO IEW VINT HILL FARMS STATION BLDG 197 WARRENTON VA 22186-5115	1	COMMANDER US ARMY SIGNAL CTR & FT GORDON ATTN ATZH CDM FT GORDON GA 30905-5090
1	PEO COMMUNICATIONS ATTN SFAE CM RE FT MONMOUTH NJ 07703-5000	1	DIRECTOR US ARMY AEROFLIGHT DYNAMICS DIR MAIL STOP 239-9 NASA AMES RESEARCH CENTER MOFFETT FIELD CA 94035-1000
1	PEO AIR DEFENSE ATTN SFAE AD S US ARMY MISSILE COMMAND REDSTONE ARSENAL AL 35898-5750	1	PROJECT MANAGER SIGNALS WARFARE ATTN SFAE IEW SG (ALAN LINDLEY) BLDG P-181 VINT HILL FARMS STATION WARRENTON VA 22186-5116
1	PEO STRATEGIC DEFENSE PO BOX 15280 ATTN DASD ZA US ARMY STRATEGIC DEFENSE CMD ARLINGTON VA 22215-0280	1	COMMANDER MARINE CORPS SYSTEMS COMMAND ATTN CBGT QUANTICO VA 22134-5080
1	PROGRAM MANAGER RAH-66 ATTN SFAE AV BLDG 5300 SPARKMAN CENTER REDSTONE ARSENAL AL 35898	1	DIRECTOR AMC-FIELD ASSIST IN SCIENCE & TECHNOLOGY ATTN AMC-FAST (RICHARD FRANSEEN) FT BELVOIR VA 22060-5606
1	JON TATRO HUMAN FACTORS SYSTEM DESIGN BELL HELICOPTER TEXTRON INC PO BOX 482 MAIL STOP 6 FT WORTH TX 76101	1	COMMANDER US ARMY FORCES COMMAND ATTN FCDJ SA BLDG 600 AMC FAST SCIENCE ADVISER FT MCPHERSON GA 30330-6000
1	CHIEF CREW SYSTEMS INTEGRATION SIKORSKY AIRCRAFT M/S S3258 NORTH MAIN STREET STRATFORD CT 06602	1	COMMANDER I CORPS AND FORT LEWIS AMC FAST SCIENCE ADVISER ATTN AFZH CSS FORT LEWIS WA 98433-5000
1	GENERAL ELECTRIC COMPANY ARMAMENT SYSTEMS DEPT RM 1309 ATTN HF/MANPRINT R C MCLANE LAKESIDE AVENUE BURLINGTON VT 05401-4985	1	HQ III CORPS & FORT HOOD OFFICE OF THE SCIENCE ADVISER ATTN AFZF CS SA FORT HOOD TX 76544-5056
1	JOHN B SHAFER 250 MAIN STREET OWEGO NY 13827	1	COMMANDER HQ XVIII ABN CORPS & FORT BRAGG OFFICE OF THE SCI ADV BLDG 1-1621 ATTN AFZA GD FAST FORT BRAGG NC 28307-5000
1	OASD (FM&P) WASHINGTON DC 20301-4000		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	SOUTHCOM WASHINGTON FIELD OFC 1919 SOUTH EADS ST SUITE L09 AMC FAST SCIENCE ADVISER ARLINGTON VA 22202	1	MS DIANE UNGVASKY HHC 2BDE 1AD UNIT 23704 APO AE 09034
1	HQ US SPECIAL OPERATIONS CMD AMC FAST SCIENCE ADVISER ATTN SOSD MACDILL AIR FORCE BASE TAMPA FL 33608-0442	1	DR SEHCHANG HAH DEPT OF BEHAVIORAL SCIENCES & LEADERSHIP BUILDING 601 ROOM 281 US MILITARY ACADEMY WEST POINT NEW YORK 10996-1784
1	HQ US ARMY EUROPE AND 7TH ARMY ATTN AEAGX SA OFFICE OF THE SCIENCE ADVISER APO AE 09014	1	US ARMY RESEARCH INSTITUTE ATTN PERI IK (DOROTHY L FINLEY) 2423 MORANDE STREET FORT KNOX KY 40121-5620
1	COMMANDER HQ 21ST THEATER ARMY AREA CMD AMC FAST SCIENCE ADVISER ATTN AERSA APO AE 09263	1	NAIC/DXLA 4180 WATSON WAY WRIGHT PATTERSON AFB OH 45433-5648
1	COMMANDER HEADQUARTERS USEUCOM AMC FAST SCIENCE ADVISER UNIT 30400 BOX 138 APO AE 09128	10	ARL HRED AVNC FIELD ELEMENT ATTN AMSRL HR MJ (D DURBIN) PO BOX 620716 BLDG 514 FT RUCKER AL 36362-0716
1	HQ 7TH ARMY TRAINING COMMAND UNIT #28130 AMC FAST SCIENCE ADVISER ATTN AETT SA APO AE 09114	1	ARL HRED MICOM FIELD ELEMENT ATTN AMSRL HR MO (T COOK) BUILDING 5400 ROOM C242 REDSTONE ARSENAL AL 35898-7290
1	COMMANDER HHC SOUTHERN EUROPEAN TASK FORCE ATTN AESE SA BUILDING 98 AMC FAST SCIENCE ADVISER APO AE 09630	1	ARL HRED USAADASCH FLD ELEMENT ATTN AMSRL HR ME (K REYNOLDS) ATTN ATSA CD 5800 CARTER ROAD FORT BLISS TX 79916-3802
1	COMMANDER US ARMY PACIFIC AMC FAST SCIENCE ADVISER ATTN APSA FT SHAFTER HI 96858-5L00	1	ARL HRED ARDEC FIELD ELEMENT ATTN AMSRL HR MG (R SPINE) BUILDING 333 PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY JAPAN/IX CORPS UNIT 45005 ATTN APAJ SA AMC FAST SCIENCE ADVISERS APO AP 96343-0054	1	ARL HRED ARMC FIELD ELEMENT ATTN AMSRL HR MH (C BIRD) BLDG 1002 ROOM 206B FT KNOX KY 40121
1	AMC FAST SCIENCE ADVISERS PCS #303 BOX 45 CS-SO APO AP 96204-0045	1	ARL HRED CECOM FIELD ELEMENT ATTN AMSRL HR ML (J MARTIN) MYER CENTER RM 3C214 FT MONMOUTH NJ 07703-5630

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	ARL HRED FT BELVOIR FIELD ELEMENT ATTN AMSRL HR MK (P SCHOOL) 10115 GRIDLEY ROAD SUITE 114 FORT BELVOIR VA 22060-5846	1	ARL HRED USAIC FIELD ELEMENT ATTN AMSRL HR MW (E REDDEN) BLDG 4 ROOM 332 FT BENNING GA 31905-5400
1	ARL HRED FT HOOD FIELD ELEMENT ATTN AMSRL HR MV HQ TEXCOM (E SMOOTZ) 91012 STATION AVE ROOM 111 FT HOOD TX 76544-5073	1	ARL HRED USASOC FIELD ELEMENT ATTN AMSRL HR MN (F MALKIN) HQ USASOC BLDG E2929 FORT BRAGG NC 28307-5000
1	ARL HRED FT HUACHUCA FLD ELEMENT ATTN AMSRL HR MY (B KNAPP) GREELY HALL (BLDG 61801 RM 2631) FORT HUACHUCA AZ 85613-5000	1	US ARMY RSCH DEV STDZN GP-UK ATTN DR MICHAEL H STRUB PSC 802 BOX 15 FPO AE 09499-1500
1	ARL HRED FLW FIELD ELEMENT ATTN AMSRL HR MZ (A DAVISON)* 3200 ENGINEER LOOP STE 166 FT LEONARD WOOD MO 65473-8929		<u>ABERDEEN PROVING GROUND</u>
2	ARL HRED NATICK FIELD ELEMENT ATTN AMSRL HR MQ (M FLETCHER) ATTN SSCNC A (D SEARS) USASSCOM NRDEC BLDG 3 RM R-140 NATICK MA 01760-5015	2	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL CI LP (TECH LIB) BLDG 305 APG AA
1	ARL HRED OPTEC FIELD ELEMENT ATTN AMSRL HR MR (D HEADLEY) PARK CENTER IV RM 1450 4501 FORD AVENUE ALEXANDRIA VA 22302-1458	1	LIBRARY ARL BLDG 459 APG-AA
1	ARL HRED SC&FG FIELD ELEMENT ATTN AMSRL HR MS (L BUCKALEW) SIGNAL TOWERS RM 207 FORT GORDON GA 30905-5233	1	USATECOM RYAN BUILDING APG-AA
1	ARL HRED STRICOM FIELD ELEMENT ATTN AMSRL HR MT (A GALBAVY) 12350 RESEARCH PARKWAY ORLANDO FL 32826-3276	1	COMMANDER CHEMICAL BIOLOGICAL AND DEFENSE COMMAND ATTN AMSCB CI APG-EA
1	ARL HRED TACOM FIELD ELEMENT ATTN AMSRL HR MU (M SINGAPORE) BLDG 200A 2ND FLOOR WARREN MI 48397-5000	1	CDN ARMY LO TO TECOM ATTN AMSTE CL TECOM HQ RYAN BLDG
1	ARL HRED USAFAS FIELD ELEMENT ATTN AMSRL HR MF (L PIERCE) BLDG 3040 RM 220 FORT SILL OK 73503-5600	1	CHIEF ARL HRED ERDEC FIELD ELEMENT ATTN AMSRL HR MM (R MCMAHON) BLDG 459 APG-AA
			<u>ABSTRACT ONLY</u>
		1	DIRECTOR US ARMY RESEARCH LABORATORY ATTN AMSRL CS AL TP TECH PUB BR 2800 POWDER MILL RD ADELPHI MD 20783-1197

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1999		3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE An Initial Assessment of the Fit, Retention, and Visual Display Characteristics of the Kaiser Proview™ Head-Mounted Display System				5. FUNDING NUMBERS AMS: 622716.H700011 PR: 1L162716AH70 PE: 6.27.16	
6. AUTHOR(S) Durbin, D.B. (ARL)					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Human Research & Engineering Directorate ATTN AMSRL HR MJ Fort Rucker, AL 36362-0716				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Human Research & Engineering Directorate Aberdeen Proving Ground, MD 21005-5425				10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARL-TN-135	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Head-mounted displays (HMDs) are a potentially viable technology for presentation of the "out-the-window" (OTW) scene for Army aviation simulators. As part of an effort to evaluate their suitability for Army aviation, a preliminary assessment of three Kaiser ProView™ HMDs was conducted during a simulation exercise at the U.S. Army Aviation Test Bed, Fort Rucker, Alabama. The assessment evaluated the fit, retention, and visual display characteristics of the HMDs. The method used to assess the HMDs included aviator responses to a usability survey, statistical correlation of survey responses with head measurements obtained from each aviator, observation of aviator performance during their missions, and post-mission interviews. Most of the fit, retention, and visual display characteristics of the HMDs were judged to be acceptable by the Army aviators. Suitability of the HMDs would be improved by an increase in field of view and the use of lightweight electrical cables to minimize restriction of head movement and potential for pressure-induced hot spots.					
14. SUBJECT TERMS anthropometry head-mounted display human factors Army aviation HMD simulation				15. NUMBER OF PAGES 50	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT		